

SPECIAL Serie

PROTECT YOUR ENVIRONMENT FROM DRAUGHTS
The Comaglio Automatic draught stoppers are removable and patented.

AE | 110 | 170/12 | 170/15 | 970 | 920 | 270 | 220

The Special Series is designed for fixing to aluminium frames, where the small size of the seal is of major importance. It is therefore possible to find within this range, a number of products well adapted to most aluminium applications. The item ref AE, new in 2006, has been added to comply with new European regulations whilst guaranteeing a speedy installation and a perfect seal to the floor.

The presence of this icon means that the product is suitable for fire stop doors.




The presence of this icon means that the product is suitable for doors with sound insulation.



AE

DOORS IN: ALUMINIUM



Components:
-Comaglio double-adjusting mechanism
-Seal designed to suit standard «Euro-groove» of aluminium door profiles (see page 14)
-Moving profile extractable
-Brass hexagonal push button
-2nd adjusting screw in brass
-2 steel return springs
-2 self-extinguishing silicon seals

Options:
-Nylon push button (round or rectangular)


Standard lengths cm:

43 Can be cut shorter by: cm.5,5

53 63 73 83 93 103 113 123 133 Can be cut shorter by: cm.10

110

DOORS IN: ALUMINIUM



Components:
-Fixed profile with minimum clearance (height 10 mm)
-Removable profile with elbow joint
-Round nylon push button
-2 steel return springs
-Black brush 48x1100

Options:
-EPDM seal

Standard lengths cm:


33 Can be cut shorter by: cm.7

43 Can be cut shorter by: cm.15

63 83 103 123 133 Can be cut shorter by: cm.20

170/12

DOORS IN: METAL ALUMINIUM PVC



Components:
-Comaglio new balancing mechanism
-Fixed profile with minimum clearance (height 12 mm)
-Moving profile extractable
-Round nylon push button
-2 steel return springs
-2 self-drilling pre-fitted screws
-Self-extinguishing silicon seal

Options:
-Brass hexagonal push button
-Rectangular nylon push button
-Special end for PVC door frames

Standard lengths cm:


33 Can be cut shorter by: cm.7 without pre-fitted screw

43 Can be cut shorter by: cm.10

53 63 73 83 93 103 113 123 133 Can be cut shorter by: cm.10

170/15

DOORS IN: METAL ALUMINIUM PVC



Components:
-Comaglio new balancing mechanism
-Fixed profile with minimum clearance (height 15 mm)
-Moving profile extractable
-Round nylon push button
-2 steel return springs
-2 self-drilling pre-fitted screws
-Self-extinguishing silicon seal

Options:
-Brass hexagonal push button
-Rectangular nylon push button
-Special end for PVC door frames

Standard lengths cm:


33 Can be cut shorter by: cm.7 without pre-fitted screw

43 Can be cut shorter by: cm.10

53 63 73 83 93 103 113 123 133 Can be cut shorter by: cm.10

920

DOORS IN:  WOOD



Components:
 -Comaglio new balancing mechanism
 -Fixed "U" shaped profile 17.7x10 mm.
 -Moving profile extractable
 -Round nylon push button
 -2 steel return springs
 -EPDM seal with 4 pressure points

Options:
 -Brass hexagonal push button
 -Black brush 48x600

Standard lengths cm:


33 Can be cut shorter by: cm.7

43 Can be cut shorter by: cm.10

63 83 103 123 133 Can be cut shorter by: cm.20

970

DOORS IN:  WOOD



Components:
 -Comaglio new balancing mechanism
 -Fixed "U" shaped profile 17.7x10 mm.
 -Moving profile extractable
 -Round nylon push button
 -2 steel return springs
 -2 self-tapping pre-fitted screws
 -EPDM seal with 4 pressure points

Options:
 -Brass hexagonal push button
 -Black brush 48x600


Standard lengths cm:

43 Can be cut shorter by: cm.9

63 83 103 123 133 Can be cut shorter by: cm.20

220

DOORS IN:  ALUMINIUM



Components:
 -Comaglio new balancing mechanism
 -Fixed profile inside moving profile
 -Moving profile extractable
 -Round nylon push button
 -2 steel return springs
 -2 neoprene seals

Options:
 -Brass hexagonal push button

Standard lengths cm:


33 Can be cut shorter by: cm.7

43 Can be cut shorter by: cm.13

63 83 103 123 133 Can be cut shorter by: cm.20

270

DOORS IN:  ALUMINIUM



Components:
 -Comaglio new balancing mechanism
 -Fixed profile inside moving profile
 -Moving profile extractable
 -Round nylon push button
 -2 steel return springs
 -2 self-drilling pre-fitted screws
 -2 neoprene seals

Options:
 -Brass hexagonal push button

Standard lengths cm:

33 Can be cut shorter by: cm.7

43 Can be cut shorter by: cm.13

63 83 103 123 133 Can be cut shorter by: cm.20



Ask technical informations about sound insulation of our draught stoppers: we can give you useful suggestions for increase acoustic performances of your door.


Comaglio®

SPECIAL Serie

Instructions page 12

Examples of application page 14

Accessories page 15

Packaging page 15