## NO SOUN

The Comaglio Automatic draught stoppers are removable and patented.

## 1770NS | 1800NS | 1370NS | ISOLA

All No Sound series have successfully passed acoustic testing in a recognised European test laboratory. The Comaglio mechanism with double adjustment, silicone hardware and reinforced profiles guarantees a perfect floor seal and therefore perfect sound insulation. It is possible to fit the this series with a silicon seal which is self-extinguishing and certified for use with on fire doors.

> The presence of this icon means that the product is suitable for fire stop doors



The presence of this icon means that the product is suitable for doors with sound insulation.



## STEEL Components: -Comaglio double-adjusting mechanism 15,6 -Fixed "U" shaped profile large 15.6 mm. -Moving profile extractable -Brass hexagonal push button -2nd adjusting screw in brass -2 steel return springs -2 self-drilling pre-fitted screws 28.3 -2 silicon seals Options: -Nylon push button (round or rectangular) -2 self-tapping pre-fitted screws -2 self-extinguishing silicon seals Standard lengths cm: 43 Can be cut shorter by: cm.7

53 63 73 83 93 103 113 123 133 Can be cut shorter by: cm.10

## STEEL Components: -Comaglio double-adjusting mechanism -Fixed "Omega" shaped profile 15,6 large 15.6 mm. -Moving profile extractable -Brass hexagonal push button -2nd adjusting screw in brass -2 steel return springs $\infty$ -2 silicon seals 28, Options: -Nylon push button (round or rectangular) -2 self-extinguishing silicon seals Standard lengths cm: 43 Can be cut shorter by: cm.12 53 | 63 | 73 | 83 | 93 | 103 | 113 | 123 | 133 | Can be cut shorter by: cm.10



